

# VN-210 GNSS/INS

## Tactical-Grade GNSS-Aided Inertial Navigation System

### Highlights

<b>0.05°-0.1°</b>	<b>0.6°/hr</b>	<b>Multi-band GNSS</b>	<b>MIL-STD VN-210</b>
Dynamic Heading Accuracy (INS)	Gyro In-Run Bias Stability	Integrated L1/L2/E1/E5b GNSS Receiver	MIL-STD-810; MIL-STD-461G; DO-160G; IP 68
<b>0.015°</b>	<b>External GNSS</b>	<b>RTK/PPK Capable</b>	<b>Low SWaP VN-210E</b>
Dynamic Pitch/Roll Accuracy (INS)	Support for external RTK/PPK & SAASM/M-Code GPS	External RTCM 3 Inputs; Exportable RINEX	31 x 31 x 12 mm; 14 grams; < 1.5 W

### Product Overview

The VN-210 is a tactical-grade, high performance GNSS-Aided Inertial Navigation System (GNSS/INS) that combines 3-axis gyros, accelerometers and magnetometers, a Multi-band L1/L2/E1/E5b GNSS receiver, and advanced Kalman filtering algorithms to provide optimal estimates of position, velocity, and attitude. The VN-210 utilizes VectorNav's proprietary onboard Extended Kalman Filter (EKF) to optimally combine high bandwidth inertial sensor measurements with high-accuracy, low bandwidth GNSS measurements to provide high-accuracy, low latency position, velocity, and attitude measurements.

The VN-210 is available in two packaging options: a precision milled, anodized aluminum enclosure (VN-210) and a miniature, board-mount option (VN-210E). With dual I/O connectors the VN-210 offers maximum flexibility for interfacing with external GNSS receivers and IMUs. For SWaP-C constrained applications, the ultra compact VN-210E option delivers unprecedented size and weight advantages while still delivering tactical-grade inertial navigation performance.



### Features

#### Industry-Leading INS

The VN-210 features VectorNav's proprietary Extended Kalman Filter INS algorithm, which is proven to excel under the most challenging dynamic conditions.

#### Robust Positioning

With support for RTK, PPK & SAASM/M-Code GPS, the VN-210 can be configured to meet the positioning requirements of a wide variety of applications.

#### True Inertial Navigation System

No mounting orientation restrictions or configuration modes; Automatic filter initialization and dynamic alignment.

#### Software Compatibility

The VN-210 and VN-210E share a common communication protocol with the entire VectorNav product line.

#### Ease of Availability

ITAR-free and Made in the USA; Short lead times.

#### User Configurable Messages

ASCII and VectorNav Binary messages.

Each individual VN-210 and VN-210E undergoes a robust calibration and acceptance testing process at VectorNav's AS9100 certified manufacturing facility. Performance specifications are based on comprehensive field testing and results from real-world applications, and are regularly tested to ensure continued conformance to such specifications.

## Sensor Summary

- ▶ VectorNav proprietary Extended Kalman Filter INS delivers coupled position, velocity, and a continuous attitude solution over the complete 360° range of operation
- ▶ Hard/Soft Iron Compensation (Real-time and Manual 2D & 3D)
- ▶ Individually calibrated for bias, scale factor, misalignment, and temperature over full operating range (-40° C to +85° C)
- ▶ RTK Capable: Support for External RTCM 3 Inputs
- ▶ Raw GNSS Data: Exportable RINEX Data for PPK; Raw Pseudorange, Doppler and Carrier Phase outputs
- ▶ Support for external RTK GNSS receivers (NovAtel, Septentrio) & SAASM/M-Code GPS receivers (ICD-GPS-153)
- ▶ Coning and sculling integrals ( $\Delta V$ 's,  $\Delta \theta$ 's)
- ▶ Data output format: ASCII (VectorNav), NMEA-0183, Binary (VectorNav), ARINC 429<sup>1</sup>
- ▶ VN-210:
  - IP 68 per IEC 60529
  - Temperature (DO-160G)
  - Electrical (MIL-STD-1275E)
  - Vibration & Shock (MIL-STD-810G)
  - EMI & Radiation (MIL-STD-461G)
- ▶ VN-210E: 24-pin 1mm pitch board-to-board interface connector with U.FL for GNSS antenna connection

## IMU Specifications

ACCELEROMETER		GYROSCOPE	MAGNETOMETER
Range <sup>9</sup>	±15 g	±490°/s (Optional ±2000°/s) <sup>9</sup>	±2.5 Gauss
In-Run Bias Stability (Allan Variance)	< 10 µg	< 1°/hr (0.6°/hr typ.)	-
Noise Density	< 0.04 mg/√Hz	5°/hr /√Hz	140 µGauss/√Hz
Bandwidth	200 Hz	210 Hz	200 Hz
Cross-Axis Sensitivity	±0.05 °	< 0.05 °	±0.05 °

## GNSS Receivers

Receiver Type.....	184 Channel, L1C/A, L1OF, E1, B1I, L2C, L2OF, E5b, B2I GNSS
Constellations <sup>10</sup> .....	GPS, GLONASS, Galileo, BeiDou, QZSS, SBAS
Time-To-First-Fix (Cold / Hot).....	29 s / 2s
Altitude Limit.....	50,000 m
Velocity Limit.....	500 m/s

## Environmental

Operating Temperature.....	-40° to +85° C
Storage Temperature.....	-40° to +85° C
MTBF (VN-210).....	> 21,000 hours
MTBF (VN-210E).....	> 22,000 hours

## Mechanical/Electrical

	SIZE	WEIGHT	INPUT VOLTAGE	CURRENT DRAW <sup>12</sup>	POWER <sup>12</sup>
VN-210	56 x 56 x 31 mm	155 g	12 to 34 V	110 mA @ 24 V	< 2.7 W
VN-210E	31 x 31 x 12 mm	14 g	3.2 to 3.5 V	420 mA @ 3.3 V	< 1.5 W

<sup>1</sup>. Contact VectorNav for ARINC 429 option.

<sup>2</sup>. With proper magnetic declination, suitable magnetic environment and valid hard/soft iron calibration.

<sup>3</sup>. Dependant on a number of factors, contact VectorNav to discuss expected performance in your application.

<sup>4</sup>. With sufficient motion for dynamic alignment.

<sup>5</sup>. Constant on a per part basis. Can be calibrated out during system integration using boresighting or other alignment processes.

<sup>6</sup>. Dependant on SBAS, clear view of GNSS satellites, good multipath environment, compatible GNSS antenna, and measurement duration period.

## Performance Specifications

### ATTITUDE

Range (Heading/Yaw, Roll).....	± 180°
Range (Pitch).....	± 90°
Heading (Magnetic) <sup>2</sup> .....	2.0° RMS
Heading (INS) <sup>3,4</sup> .....	0.05° to 0.1°, 1σ
Pitch/Roll (Static).....	0.05° RMS
Pitch/Roll (INS) <sup>4</sup> .....	0.015°, 1σ
Heading Mounting Misalignment (VN-210) <sup>5</sup> .....	< 0.05°, 1σ
Heading Mounting Misalignment (VN-210E) <sup>5</sup> .....	0.15°, 1σ
Pitch/Roll Mounting Misalignment <sup>5</sup> .....	< 0.05°, 1σ
Angular Resolution.....	0.001°

### POSITION/VELOCITY

Horizontal Position Accuracy <sup>6</sup> .....	1.0 m RMS
Vertical Position Accuracy <sup>6</sup> .....	1.5 m RMS
RTK Position Accuracy <sup>7</sup> .....	0.01 m + 1 ppm CEP
Free Inertial Position Drift <sup>8</sup> .....	0.5 cm/s <sup>2</sup>
Velocity Accuracy.....	< 0.02 m/s

### GYROSCOPE

±490°/s (Optional ±2000°/s)<sup>9</sup>

±2.5 Gauss

### MAGNETOMETER

140 µGauss/√Hz

### GYROSCOPE

5°/hr /√Hz

### MAGNETOMETER

200 Hz

## Interfacing

Output Data Rate (IMU) <sup>11</sup> .....	up to 800 Hz
Output Data Rate (Position, Velocity & Attitude).....	up to 400 Hz
Primary Interface (VN-210).....	RS-422 (Optional RS-232)
Auxiliary Interface (VN-210).....	RS-422
Interface (VN-210E).....	(2) Serial TTL
GNSS PPS.....	30 ns RMS, 60 ns 99%
Input.....	Sync-in
Output.....	Sync-out